

SUAY19 经济型压力变送器

SUAY19

与

不



适用范围：

产品特点

- -100KPa 40MPa
-
-
-
-
-
-

产品性能指标

	-100KPa-0-100KPa...1MPa...40MPa ()
	与 316 不
①	±0.5%FS () ±1%FS ()
/	4-20mA 0-5V 1-5V 12-30VDC(24VDC)
	0.5-4.5V 5VDC/12-30VDC(24VDC)
	-10 ~ 85°C
	0 ~ 60°C
	-40 ~ 100°C

: $\pm 0.2\%FS/$: $\pm 0.3\%FS/$
: $\pm 0.02\%FS/^\circ C$: $\pm 0.05\%FS/^\circ C$
: $\pm 0.02\%FS/^\circ C$: $\pm 0.05\%FS/^\circ C$
2	
10^6 (P:10-90%FS)	
20g (IEC 60068-2-6)	
20g , 11mS	
≤ 1 ms	
10^{-5} (,)	
$\leq (U-12) / 0.02 \Omega$ ()	$> 100K\Omega$ ()
200M Ω , 100VDC	
M20*1.5 G1/4 ()	
2m ()	
304/316L 不	
IP65 ()	IP67 ()
Ex iaII CT6 ()	
不 316L	
200	

: ①

选型参数对照表

SUAY19	-100KPa~0 ...100KPa ...40MPa	1: $\pm 0.5\%FS$ 0: $\pm 1\%FS$	A1:4-20mA V1:0-5V V2:1-5V V4:0.5-4.5V	M1:M20*1.5 M2:G1/2	N1: 2 : N2:	S: L: E:
SUAY19.1.A1.M1.N1						

选型提示 :

1. 与 ,
2. "E" ,
3. , 与 ,